














Seafreight: Container Specifications

EQUIPMENT	INTERIOR DIMENSIONS	DOOR OPENING	TOP OPENING	TARE WEIGHT	CUBIC CAPACITY	PAYLOAD*
 45' High Cube Container	L: 13.582 m 44' 6 1/2" W: 2.347 m 7'8.25" H: 2.690 m 8'10"	W: 2.347 m 7'8 1/4" H: 2.584 m 8'5 3/4"		4,110 kg 9,061 lbs.	85.7 cbm. 3,026 cu. ft.	28,390 kg 62,589 lbs.
 40' High Cube Container	L: 12.056 m 39' 6 1/2" W: 2.347 m 7'8 1/4" H: 2.684 m 8'9 1/2"	W: 2.340 m 7'8" H: 2.585 m 8'5 3/4"		2,900 kg 6,393 lbs.	76.0 cbm. 2,684 cu. ft.	29,600 kg 65,256 lbs.
 40' Dry Freight Container	L: 12.051 m 39' 6 1/2" W: 2.340 m 7'8" H: 2.380 m 7'9 1/2"	W: 2.286 m 7'6" H: 2.278 m 7'5 1/2"		3,084 kg 6,799 lbs. 3,630 kg (steel) 8,003 lbs. (steel)	67.3 cbm. 2,377 cu. ft.	27,397 kg 60,401 lbs.
 20' Dry Freight Container	L: 5.919 m 19' 5" W: 2.340 m 7'8" H: 2.380 m 7'9 1/2"	W: 2.286 m 7'6" H: 2.278 m 7'5 1/2"		1,900 kg 4,189 lbs.	33.0 cbm. 1,165 cu. ft.	22,100 kg 48,721 lbs.
 20' Open Top Container	L: 5.919 m 19' 5" W: 2.340 m 7'8" H: 2.380 m 7'9 1/2"	W: 2.286 m 7'6" H: 2.251 m 7'4 1/2"	L: 5.425 m 17'9 1/2" W: 2.222 m 7'3 1/2"	2,174 kg 4,793 lbs.	31.6 cbm. 1,116 cu. ft.	21,826 kg 48,117 lbs.
 40' Open Top Container	L: 12.043 m 39' 6" W: 2.338 m 7'8" H: 2.272 m 7'5 1/4"	W: 2.279 m 7'5 1/2" H: 2.272 m 7'5 1/4"	L: 11.585 m 38' 1/2" W: 2.162 m 7'1"	4,300 kg 9,480 lbs.	64.0 cbm. 2,260 cu. ft.	26,181 kg 57,720 lbs.
 45' High Cube Reefer Container	L: 13.102 m 42'11 13/16" W: 2.294 m 7'6 5/16" H: 2.509 m 8'2 3/4"	W: 2.467 m 8'1 1/8" H: 2.290 m 7'6 1/8"		5,200 kg 11,464 lbs.	75.4 cbm. 2,663 cu. ft.	28,350 kg+ 62,370 lbs.+
 40' High Cube Reefer Container	L: 11.557 m 37'11" W: 2.286 m 7'6" H: 2.491 m 8'2"	W: 2.286 m 7'6" H: 2.454 m 8'1 1/2"		4,320 kg 9,524 lbs.	65.8 cbm. 2,324 cu. ft.	28,180 kg 62,126 lbs.
 40' Reefer Container	L: 11.207 m 36'9" W: 2.246 m 7'4" H: 2.183 m 7'2"	W: 2.216 m 7'3" H: 2.183 m 7'2"		4,600 kg 10,141 lbs.	54.9 cbm. 1,940 cu. ft.	25,881 kg 57,059 lbs.
 20' Flat Rack Container	L: 5.702 m 18'8 1/2" W: 2.438 m 8' H: 2.327 m 7'7 1/2"			2,330 kg 5,137 lbs.		21,670 kg 47,773 lbs.
 40' Flat Rack Container	L: 11.820 m 38'9 1/4" W: 2.148 m 7'6" H: 2.095 m 6'10 1/2"			5,260 kg 11,596 lbs.		25,220 kg 55,660 lbs.
 40' Artificial Tweendeck	L: 12.065 m 39'7" W: 2.216 m 7'3 1/4"			5,400 kg 11,905 lbs.		39,000 kg 85,979 lbs.
 40' Collapsible Flat Rack	L: 12.08 m 39'7 1/2" W: 2.216 m 6'11 1/2" H: 2.043 m 6'8 1/4"			5,800 kg 12,787 lbs.		29,200 kg 64,374 lbs.

* Payload details are subject to prevailing over-the-road weight limitations applicable in individual countries and states. + Payload varies _ check container doors.

Dimensions are approximate and do vary depending on manufacturing specifications. Actual loading capacity approximately 85% of maximum, depending on carton size.